

Coffee System PrecisionBrew warmer shuttle double brewer

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


600674 (EPBC2W2)

PrecisionBrew warmer shuttle brewer, double - shuttles to be ordered separately

Short Form Specification

Item No. _____

Double PrecisionBrew warmer shuttle brewer that brews into 5.7lt vacuum shuttle. Shuttles® sensor prevents brewing when server is not in place. Digitally controlled with PrecisionBrew™ Technology. Advanced touchscreen digital interface simplifies and streamlines brewing and operation.

Main Features

- Sensor prevents brewing when shuttle is not in place.
- Machine knows if brew basket is installed.
- Digitally controlled with PrecisionBrew™ Technology.
- Intuitive, icon-driven touchscreen digital interface simplifies and streamlines brewing and operation.
- Reimagined modern design for PrecisionBrew™: single and double sightglass models brew into 5.7 L warmer Shuttle(s)®.

Included Accessories


- 2 of Stainless steel coffee brew basket PNC 870059

Optional Accessories


- Remote warmer shuttle stand used with shuttle EWS15 PNC 600680
- 5,7 lt Warmer shuttle used with brewers EPBC1W2, EPBC1W2UK, EPBC2W2, EPBC2W2UK PNC 600682
- Shuttle graphics for warmer Precision Brewers used with shuttle EWS15 PNC 870017
- Filter paper, 35,5x15,2 cm (500 pieces per box) PNC 870024
- Plastic coffee brew basket PNC 870040

APPROVAL: _____


Front



Side



Top



Electric

Supply voltage:

600674 (EPBC2W2) 230 V/1N ph/50/60 Hz

Electrical power max.:

2.8 kW

Key Information:

External dimensions, Width: 460 mm

External dimensions, Height: 852 mm

External dimensions, Depth: 486 mm

Net weight: 34 kg

Shipping weight: 36 kg

Shipping height: 784 mm

Shipping width: 587 mm

Shipping depth: 654 mm

Shipping volume: 0.3 m³