



Technical data:

Electrical connection: 220-240 VAC, 1LNPE, 0,30 A, 10 A, 50 Hz
 220 VAC, 1LNPE, 0,35 A, 10 A, 60 Hz
 Energy loss: 0,571 kWh/24h - 220-240 VAC, 50 Hz (according to DIN 18873-2)
 Temperature range: + 3°C to + 8°C (Milk)
 Net weight: up to max. 27 kg
 Noise emission: < 70 dB (A)
 Refrigerant: R600a 11g (0,39oz)

Installation notes on site:

Soket with RCD (residual current device)
 220-240 VAC, 1L N PE, 10 A, 50 Hz
 220 VAC, 1L N PE, 10 A, 60 Hz

The cooling unit must be installed under the coffee machine.
 The supply lines are run through the tabletop under the cooling unit.
 Wall clearance of the rear panel min. 50 mm, of the side panels min. 20 mm.

Installation requirements:

Our delivered appliances are ready for operation. They have to be installed on a flat surface. First the preparations for the connections of water and electricity must be complete. Distance max. 1 m up to the device. This preparation-works must be performed by qualified specialists in accordance with applicable regulations. The device is intended exclusively for operation in interior rooms. Ambient temperatur: 5°C - 32°C. Humidity: max. 80%

Unit	mm	Scale	NTS	Description	TD_UC09_EC_en								
Drawn	MB002	09.04.2021		Fränke Kaffeemaschinen AG Fränke-Strasse 9 CH-4963 Aarburg Telefon: +41 (0) 787 3607 E-Mail: smuch@franke.com Internet: www.franke.com									
Modified	MB002	09.04.2021		These drawings and specifications are the property of Fränke Technology and Trademark Ltd. and shall not be reproduced, copied or transferred in any form without the prior written permission of Fränke Technology and Trademark Ltd., Heggen, Switzerland									
Checked		01.01.1970		ECN	500000001512	Document ID - Version	20205200-01	Revision	15	Status	1 / 1	Format	A2